



Dimension: mm NTS



**Surface Mount  
Semi-recessed  
Weatherproof  
Emergency Luminaire**



**IP65  
CLASS 1**

### » Technical Data

Mode of operation	: Non-maintained and others
Lamp	: 2 x 8W fluorescent lamp
Rated duration	: 2 hr and others
Mains supply	: 230 Volts, 50/60Hz
Power consumption	: 3VA
Battery	: High temp nickel cadmium
Charge monitor	: Red LED ø5mm
Test facility	: Push-off test switch
Safety feature	: Low volt cut-off preventing battery overdischarge
Housing & cover	: Injection moulded fire retardant high impact polycarbonate
Mounting	: Wall, ceiling or semi-recessed
Cable entry	: ø20mm K/O hole
Weight	: 2kg (gross)
Compliance	: CP19, SS263 : Part 2, IEC 598-2-22
Warranty	: 1 year

### » Ordering Guide

Please check with Sales Dept if customisation is required

Model	Lamp (watt)
MC/NM/108	1 x 8
MC/NM/208	2 x 8
MC/NM/110	1 x 10
MC/NM/PL18	1 x PL18
MC/NM/PL24	1 x PL24

Note:

All above specifications are available in other mode of operations.

Specifications subject to changes without prior notice