





PP203L NC



Dimension: mm NTS

High Power L.E.D
from LUMILEDS



Surface Mount
Flexible Application
Emergency Luminaire



IP50
CLASS 2

» Technical Data

Mode of operation	: Non-Maintained
Lamp	: 2 x 1W Light Emitting Diode (LED)
Rated duration	: 2 hr and others
Mains supply	: 230 Volts, 50/60Hz
Power consumption	: 2VA
Battery	: High temp nickel cadmium
Charge monitor	: Red LED ø5mm
Test facility	: Rocker switch
Safety feature	: Low volt cut-off preventing battery overdischarge
Housing	: High impact thermoplastic enclosure in a matt white finish. Transparent half cylinder Polycarbonate lamp shield with fresnel pattern and fully adjustable self-locking lamp heads
Mounting	: Wall or ceiling. The snap-fit design facilitate and fast installations. Easily removable mounting and knockout hole are provided (fitting can be positioned vertically or horizontally)
Cable entry	: ø20mm K/O hole
Weight	: 1.3kg (gross)
Compliance	: CP19, SS263 : Part 2, IEC 598-2-22
Warranty	: 1 year

» Ordering Guide

Please check with Sales Dept if customisation is required

Model	Lamp (watt)	Battery type
PP203L NC	2 x 1 LED	Nickel cadmium

» Key Features

- high brightness output
- low power consumption
- low maintenance
- high lumen/watt efficiency
- long lifespan

Specifications subject to changes without prior notice