



Dimension: mm NTS



**430 x 62mm**

**Recess Mount  
Slim Exit Sign**



**IP30  
CLASS 1**

## » Technical Data

Mode of operation	: Maintained
Lamp	: 1 x 8W fluorescent lamp
Rated duration	: 2 hr and others
Mains supply	: 230 Volts, 50/60Hz
Power consumption	: 10VA
Battery	: High temp nickel cadmium
Charge monitor	: Red LED ø5mm
Test facility	: Micro switch
Safety feature	: Low volt cut-off preventing battery overdischarge
Fitting construction	: Electro galvanised steel with epoxy powder coating
Diffuser	: Fire retardant moulded acrylic
Mounting	: Recess
Cable entry	: ø20mm K/O hole
Weight	: 2.8kg (gross)
Compliance	: CP19, SS263 : Part 2, IEC 598-2-22, SS 508
Warranty	: 1 year

## » Ordering Guide

Please check with Sales Dept if customisation is required

Single Sided	Double Sided	Legend
MSSR/M/1080	MSDR/M/1080	
MSSR/M/108R	MSDR/M/108R	
MSSR/M/108L	MSDR/M/108R	
MSSR/M/108RM	MSDR/M/108RM	
MSSR/M/108E	MSDR/M/108E	
MSSR/M/108W	MSDR/M/108E	
MSSR/M/108S	MSDR/M/108S	
MSSR/M/108N		

Specifications subject to changes without prior notice